ITALAUTOCAR
tecnologie e componenti

Modulo di commessa per fornitura cassette porta attrezzi

Customized toolboxes form

Ordine: Order: ☐	**Offerta:** Offer: ☐	**Cliente:** Customer: _____	**Data:** Date: _____



Standard



☐

Lat. dx / Right side



☐

Lat. sx / Left side



☐

Apertura a baule chiusura a laccio lucchettabile
Case opening with lockable closing



Fondo girato
Turned bottom
☐

Fondo standard
Standard bottom
☐

2 sport / 2 doors



☐

Bilat. / Double-side



☐

Bilat. controvento
Double-side brace



☐

Chiusura PVC nera con chiave
Black PVC key-lock ☐

Chiusura tipo frigo con chiave
Refrigerator-type key-lock ☐

Chiusura Europa INOX
Padlock-type closing ☐

L= _____

P= _____

H= _____

Materiale: / Material:

Lam. Fe/Zn: Sheet metal Fe/Zn: ☐

Lam. inox: Sheet metal stainless st.: ☐

Laminox fiorettato: Sheet metal anti-reflex stainless st.: ☐

Spessore: / Thickness:

8/10 ☐ 15/10 ☐
10/10 ☐ 20/10 ☐
12/10 ☐

OPZIONI

Cerniera continua / Continuous hinge ☐

Ripiano centrale / Central shelf ☐

(indicare distanza da sotto) / (note the distance from below) _____

Divisoria verticale / vertical partition ☐

Data di consegna: / Delivery date: _____

Quantità: / Quantity: _____

Codice: / Code: _____

Eventuale scritta su sportello / Possible writing on the door _____

Note produttive: / Manufacturing features:

L < 800 1ch
L > 800 2ch
L > 1500 < 2000 3ch
L > 2000 4ch

Sp. lamiera consigliato in funzione del Volume
Sheet metal thickness recommended according to volume

Calcolo Volume cassetta
Box volume calculation

Le misure vanno espresse in dm
Measures must be indicated in dm
(Es:800mm = 8dm; Ex:800mm = 8dm**)**

Vol.=dm³ < 160 sp = 8/10
Vol.=dm³ > 160 < 300 sp = 10/10
Vol.=dm³ > 300 < 500 sp = 12/10
Vol.=dm³ > 500 < 800 sp = 15/10
Vol.=dm³ > 800 sp = 20/10

Timbro e firma per approvazione
Stamp and signature for approval

ITALAUTOCAR S.r.l. Via Leonardo da Vinci, 23 • 41015 NONANTOLA (MO) Italy
Tel. +39 059 54.52.87 (6 linee r.a.) • Fax +39 059 54.63.26 • www.italautocar.com • info@italautocar.com